Double insulated housing with built-in NCV (Non-Contact Voltage) tester

Features:

- 1.5" (40mm) Jaw opening fits conductors up to 500 MCM
- Measures Current, Voltage, Resistance, Temperature, Capacitance, Continuity, Diode Test
- Large backlit easy-to-read 6000 count LCD display
- Auto Power Off and low battery indicator
- Auto and manual ranging with min/max hold
- Double insulated housing is splash proof, dust proof and drop resistant
- Well suited for a variety of industrial and residential applications such as security, electrical, HVAC installations and more.
- Includes test leads, Type K Temperature probe, 9V battery, and case
- Optional model complete with Certificate of Traceability to N.I.S.T.
- 3-year warranty

Snecifications

Specifications	
True RMS/Averaging	True RMS
Display Counts	6000 with analog bargraph
Clamp Size	1.5" (40mm)
AC Current	0.1 to 1000A
ACA Accuracy	±2.8%
DC Current	0.1 to 1000A
AC Voltage	1mV to 600V
DC Voltage	1mV to 600V
Resistance	0.1Ω to 60MΩ
Temperature	-4 to 1400°F (-20 TO 760°c)
Capacitance	0.01nF to 4000µF
Frequency	0.01Hz to 10kHz
Duty Cycle	0.1 to 99.9%
Safety Category	CAT III-600V
Dimensions	9.5 x 2.75 x 1.5" (232 x 77 x 39mm)
Weight	11.2oz (271g)

Ordering Information:

9325	True RMS Clamp-On Meter
9325-NIST	9325 Including Certificate of Traceability to N.I.S.T.









